

# TAHAN

CARPET TILE





# *Introduction*

Elevate your floor with **Panache** Graphic design Carpet tile

## "TAHAN"

thanks to the combination of two Contrasting colours into One Carpet tile.

This inspirational collection enables to create unique layout perfect for office,

retail space or any area that needs a creative touch,

Our Carpet tiles are easy to install, to maintain,

while bringing comfort & softness to the floor.





TH 5141





TH 5151





















TH5161



CONFERENCE CENTER  
会议中心

TH 5164





TH 5141

TH 5151

TH 5161

TH 5164



| TECHNICAL SPECIFICATION |                           |
|-------------------------|---------------------------|
| Construction            | Multi-level loop with Cam |
| Fiber                   | 100% PP AIR- ENTANGLED    |
| Gauge                   | 1/12"                     |
| Pile Weight             | 520gsm                    |
| Total Height            | 5-6mm                     |
| Package                 | 5sqms / box               |
| Primary Backing         | Non-woven                 |
| Secondary Backing       | PVC with glass fiber      |
| Size Per Tile           | 50cm x 50 cm              |

| PERFORMANCE SPECIFICATION |                                 |
|---------------------------|---------------------------------|
| FLAMMABILITY TESTS        |                                 |
| Radiant Panel             | Pass - Class I (ASTM E 648-17)  |
| Methenamine Pill          | Pass - 8 (ASTM D 2859-16)       |
| Smoke Density             | Pass - Max 450 (ASTM E 662-15a) |
| STABILITY                 |                                 |
| Dimensional Stability     | Pass - 0.2% (ASTM D7570)        |
| Tuft Bind                 | Pass - 6.2 lbs (ASTM D1335)     |
| Static Propensity         | Pass - 1.1KV (AATCC 134-2011)   |
| Light                     | Pass - Level 4 (AATCC 16.3)     |
| Rubbing/Crocking          | Pass - Level 5 (AATCC 165)      |
| Hexpad Drum               | Pass - 2 (ASTM D5252)           |

## MAINTENANCE

- Vacuuming is the most important cleaning procedure. Effective vacuuming prevents soil from spreading through the carpet tile.
- Correct and regular maintenance will increase the lifespan of a carpet tile and also helps to maintain its appearance.
- Cleaning should be proportional to the amount of soiling to which the carpet tile is subjected.
- For a heavy soiled carpet tile, professional cleaning is recommended.
- Technically, carpet tile pigments are better, but color's may fade. If possible the carpet tile should be protected from intense, direct sunlight.
- To reduce soiling and wear high traffic areas, place walk-off mats at all entrances. These must be cleaned and rotated regularly.
- Specification are Subject to  $\pm$  5% variation.
- Shading or Pile reversal is nature of carpet and it is not a manufacturing defect.
- Color may slightly vary from one dye lot to another dye lot.



Sound Insulation



Heat Insulation



Anti-static



Colorfast



Wearproof



Anti-flammability



ASHLAR



DIRECTIONAL



BRICK



QUARTER TURN



  
**Panache**<sup>®</sup>  
*Where Style meets Comfort*

